

# Using FeatureExtraction (Korean)

Jeon Ga Bin & Martijn J. Schuemie

2025-09-01

## 1

FeatureExtraction CohortMethod PatientLevelPrediction  
FeatureExtraction

## 2

- 1.
- 2.
- 3.

ID (cohort start) — ( 1) ( 2) ( 3)  
ID ID ID ( : Charlson Comorbidity ). ID

### 2.1

```
settings <- createDefaultCovariateSettings()
```

```
settings <- createDefaultCovariateSettings(
  excludedCovariateConceptIds = 1124300,
  addDescendantsToExclude = TRUE
)
```

1124300( ) ( , ) .

## 2.2

createCovariateSettings .

createCovariateSettings

:

```
settings <- createCovariateSettings(
  useDemographicsGender = TRUE,
  useDemographicsAgeGroup = TRUE,
  useConditionOccurrenceAnyTimePrior = TRUE
)
```

, (5 ) ( ) — .

- : 365 .
- : 180 .
- : 30 .

:

```
settings <- createCovariateSettings(
  useConditionEraLongTerm = TRUE,
  useConditionEraShortTerm = TRUE,
  useDrugEraLongTerm = TRUE,
  useDrugEraShortTerm = TRUE,
  longTermStartDays = -180,
  shortTermStartDays = -14,
  endDays = -1
)
```

180 ( ) 14 ( ) .

ID .

```
settings <- createCovariateSettings(
  useConditionEraLongTerm = TRUE,
  useConditionEraShortTerm = TRUE,
  useDrugEraLongTerm = TRUE,
  useDrugEraShortTerm = TRUE,
  longTermStartDays = -180,
```

```

shortTermStartDays = -14,
endDays = -1,
excludedCovariateConceptIds = 1124300,
addDescendantsToExclude = TRUE
)

```

## 2.3

### SQL

```

settings <- createCovariateSettings(useConditionEraLongTerm = TRUE)
settings2 <- convertPrespecSettingsToDetailedSettings(settings)
settings2$analyses[[1]]

```

```

## $analysisId
## [1] 202
##
## $sqlFileName
## [1] "DomainConcept.sql"
##
## $parameters
## $parameters$analysisId
## [1] 202
##
## $parameters$analysisName
## [1] "ConditionEraLongTerm"
##
## $parameters$startDay
## [1] -365
##
## $parameters$endDay
## [1] 0
##
## $parameters$subType
## [1] "all"
##
## $parameters$domainId
## [1] "Condition"
##
## $parameters$domainTable
## [1] "condition_era"
##
## $parameters$domainConceptId
## [1] "condition_concept_id"
##
## $parameters$domainStartDate
## [1] "condition_era_start_date"
##
## $parameters$domainEndDate
## [1] "condition_era_end_date"
##
## $parameters$description

```

```
## [1] "One covariate per condition in the condition_era table overlapping with any part of the long te
##
##
## $includedCovariateConceptIds
## list()
##
## $includedCovariateIds
## list()
##
## $addDescendantsToInclude
## [1] FALSE
##
## $excludedCovariateConceptIds
## list()
##
## $addDescendantsToExclude
## [1] FALSE
```

```
analysisDetails <- createAnalysisDetails(
  analysisId = 1,
  sqlFileName = "DemographicsGender.sql",
  parameters = list(
    analysisId = 1,
    analysisName = "Gender",
    domainId = "Demographics"
  ),
  includedCovariateConceptIds = c(),
  addDescendantsToInclude = FALSE,
  excludedCovariateConceptIds = c(),
  addDescendantsToExclude = FALSE,
  includedCovariateIds = c()
)

settings <- createDetailedCovariateSettings(list(analysisDetails))
```

## 2.4

(: , , ) .

365 .

ID ID CohortMethod .

PatientLevelPrediction .

```
settings <- createDefaultTemporalCovariateSettings()
```

,

```
settings <- createTemporalCovariateSettings(
  useConditionOccurrence = TRUE,
  useMeasurementValue = TRUE
)
```

condition\_occurrence , CDM measurement  
365 ( ) 7 .

```
settings <- createTemporalCovariateSettings(
  useConditionOccurrence = TRUE,
  useMeasurementValue = TRUE,
  temporalStartDays = seq(-364, -7, by = 7),
  temporalEndDays = seq(-358, -1, by = 7)
)
```

```
analysisDetails <- createAnalysisDetails(
  analysisId = 1,
  sqlFileName = "MeasurementValue.sql",
  parameters = list(
    analysisId = 1,
    analysisName = "MeasurementValue",
    domainId = "Measurement"
  ),
  includedCovariateConceptIds = c(),
  addDescendantsToInclude = FALSE,
  excludedCovariateConceptIds = c(),
  addDescendantsToExclude = FALSE,
  includedCovariateIds = c()
)

settings <- createDetailedTemporalCovariateSettings(list(analysisDetails))
```

### 3

, diclofenaca cellecoxi .

#### 3.1

R . CohortMethod createConnectionDetails DatabaseConnector  
(DBMS) createConnectionDetails PostgreSQL .

```
connectionDetails <- createConnectionDetails(
  dbms = "postgresql",
  server = "localhost/ohdsi",
  user = "joe",
  password = "supersecret"
)
```

```
cdmDatabaseSchema <- "my_cdm_data"
resultsDatabaseSchema <- "my_results"
```

```
cdmDatabaseSchema resultsDatabaseSchema . CDM , R
. Microsoft SQL Server cdmDatabaseSchema <- "my_cdm_data.dbo"
```

## 3.2

```
FeatureExtraction 365 . FeatureExtraction . SQL 1
```

```

/*****
File cohortsOfInterest.sql
*****/

IF OBJECT_ID('@resultsDatabaseSchema.cohorts_of_interest', 'U') IS NOT NULL
  DROP TABLE @resultsDatabaseSchema.cohorts_of_interest;

SELECT first_use.*
INTO @resultsDatabaseSchema.cohorts_of_interest
FROM (
  SELECT drug_concept_id AS cohort_definition_id,
         MIN(drug_era_start_date) AS cohort_start_date,
         MIN(drug_era_end_date) AS cohort_end_date,
         person_id
  FROM @cdmDatabaseSchema.drug_era
  WHERE drug_concept_id = 1118084 -- celecoxib
         OR drug_concept_id = 1124300 -- diclofenac
  GROUP BY drug_concept_id,
           person_id
) first_use
INNER JOIN @cdmDatabaseSchema.observation_period
  ON first_use.person_id = observation_period.person_id
  AND cohort_start_date >= observation_period_start_date
  AND cohort_end_date <= observation_period_end_date
WHERE DATEDIFF(DAY, observation_period_start_date, cohort_start_date) >= 365;
```

```
Sql SqlRender . SQL . SQL CDM . SQL
. SQL . SqlRender SQL .
```

```
library(SqlRender)
sql <- readSql("cohortsOfInterest.sql")
sql <- render(sql,
  cdmDatabaseSchema = cdmDatabaseSchema,
  resultsDatabaseSchema = resultsDatabaseSchema
)
sql <- translate(sql, targetDialect = connectionDetails$dbms)

connection <- connect(connectionDetails)
executeSql(connection, sql)
```

SQL . . . SQL DBMS . ,

SQL . . .

```
sql <- paste(
  "SELECT cohort_definition_id, COUNT(*) AS count",
  "FROM @resultsDatabaseSchema.cohorts_of_interest",
  "GROUP BY cohort_definition_id"
)
sql <- render(sql, resultsDatabaseSchema = resultsDatabaseSchema)
sql <- translate(sql, targetDialect = connectionDetails$dbms)

querySql(connection, sql)
```

```
## cohort_concept_id count
## 1 1124300 240761
## 2 1118084 47293
```

### 3.3 1

1 .

```
covariateSettings <- createDefaultCovariateSettings()

covariateData <- getDbCovariateData(
  connectionDetails = connectionDetails,
  cdmDatabaseSchema = cdmDatabaseSchema,
  cohortDatabaseSchema = resultsDatabaseSchema,
  cohortTable = "cohorts_of_interest",
  cohortIds = c(1118084),
  rowIdField = "subject_id",
  covariateSettings = covariateSettings
)

summary(covariateData)
```

#### 3.3.1

covariateData .

covariateData\$covariates

- rowId . getDbCovariateData rowIdField = "subject\_id" rowId
- subject\_id . rowId
- covariate covariates cohortData\$covariateRef .
- covariateValue .

### 3.3.2

`saveCovariateData(covariateData, "covariates")`

`loadCovariateData()`

`tidyCovariateData`

### 3.3.3

`tidyCovariates <- tidyCovariateData(covariateData, minFraction = 0.001, normalize = TRUE, removeRedundancy = TRUE)`

`metaData`

`deletedCovariateIds <- tidyCovariates$metaData$deletedInfrequentCovariateIds`

`head(deletedCovariateIds)`

`metaData`

`deletedCovariateIds <- tidyCovariates$metaData$deletedRedundantCovariateIds`

### 3.4

`aggregateCovariates(covariateData)`

`createDefaultCovariateSettings()`

`getDbCovariateData`

`connectionDetails = connectionDetails,`

`cdmDatabaseSchema = cdmDatabaseSchema,`



```

cohortDatabaseSchema = resultsDatabaseSchema,
cohortTable = "cohorts_of_interest",
cohortIds = c(1118084),
covariateSettings = covariateSettings,
aggregated = TRUE
)
summary(covariateData2)

```

aggregated = TRUE      .      personId      rowIdField      .

### 3.4.1

covariateData      .

```
covariateData2$covariates
```

```
covariateData2$covariatesContinuous
```

covariates

- covariateId      ,      cohortData\$covariateRef
- sumValue      .      ,      1      .
- averageValue      .      ,      1

covariatesContinuous

- covariateId      ,      cohortData\$covariateRef
- countValue      (      )
- minValue,maxValue,averageValue,standardDeviation,medianValue,p10Value,p25Value,p75Value,p90Value  
     .      ( : Charlson comorbidity index)      0      0      ( : )      0  
     .      covariateData\$analysisRef      missingMeansZero      .

## 3.5      1

    .      ' 1'      .      1      .

```

result <- createTable1(
  covariateData1 = covariateData2,
  output = "one column"
)
print(result, row.names = FALSE, right = FALSE)

```

    ,      ,      365      .      createTable1      .  
 getDefaultTable1Specifications      .      ID      ID      ID      ID      .      1      .  
     covariateData      1      .      createTable1CovariateSettings

```

covariateSettings <- createTable1CovariateSettings()

covariateData2b <- getDbCovariateData(
  connectionDetails = connectionDetails,
  cdmDatabaseSchema = cdmDatabaseSchema,
  cohortDatabaseSchema = resultsDatabaseSchema,
  cohortTable = "cohorts_of_interest",
  cohortIds = c(1118084),
  covariateSettings = covariateSettings,
  aggregated = TRUE
)
summary(covariateData2b)

```

4.

1

```

settings <- createTable1CovariateSettings(
  excludedCovariateConceptIds = c(1118084, 1124300),
  addDescendantsToExclude = TRUE
)

covCelecoxib <- getDbCovariateData(
  connectionDetails = connectionDetails,
  cdmDatabaseSchema = cdmDatabaseSchema,
  cohortDatabaseSchema = resultsDatabaseSchema,
  cohortTable = "cohorts_of_interest",
  cohortIds = c(1118084),
  covariateSettings = settings,
  aggregated = TRUE
)

covDiclofenac <- getDbCovariateData(
  connectionDetails = connectionDetails,
  cdmDatabaseSchema = cdmDatabaseSchema,
  cohortDatabaseSchema = resultsDatabaseSchema,
  cohortTable = "cohorts_of_interest",
  cohortIds = c(1124300),
  covariateSettings = settings,
  aggregated = TRUE
)

std <- computeStandardizedDifference(covCelecoxib, covDiclofenac)

```

celecoxib (1118084) diclofenac (1124300)

```
head(std)
```

stdDiff

1

```
result <- createTable1(  
  covariateData1 = covCelecoxib,  
  covariateData2 = covDiclofenac,  
  output = "two columns"  
)  
print(result, row.names = FALSE, right = FALSE)
```